

Architectural floor plan of a bathroom (WC) showing two shower stalls and two toilet stalls. The plan includes dimensions for the room (10.00m x 4.95m), shower stalls (2.225m x 1.20m), and toilet stalls (2.225m x 0.75m). It shows the layout of fixtures, including showers, toilets, and a sink. Annotations include 'Wody popłuczne z budynku filtrów' (Flush water from building filter) and 'dopływ wg. proj. sieci międzyobiektowych' (Supply according to inter-object network project). The plan also indicates a 1% slope for the floor.

— wody popłuczne oczyszczone  
— wody popłuczne – dopływ

Lp	Opis elementu	Jednostka	Ilość
1	Konstrukcja żelbetowa osadnika dwukomorowego, kompletna z balustradami, drabinkami, zejściowymi, pochwytyami. Kompletnie wg. projektu branży konstrukcyjnej	kpl	1
2	Komora wlotowa osadnika wykonana z blacy stalowej nierdzewnej 3mm, o wymiarach: szerokość 0,5m, długość 1,2m, wysokość 0,6m, otwory Ø80 co 0,25m, wg rysunku.	kpl	2
3	Zasuwa nożowa, międzykołnierzowa, DN200, szczelność w jednym kierunku, z przedłużonym trzpieniem o 0,75m, z kółkiem ręcznym	kpl	2
4	Tuleja kołnierzowa PE100 Ø200, SDR17, komplet z pierścieniem PN10, uszczelką i śrubami	kpl	2
5	Kołnierz do połączeń skręcanych DN200 ze stali nierdzewnej, komplet z uszczelką, PN10	kpl	2
6	Przeście szczelne tańczuchowe dla rury Ø200 i otworu Ø250, kompletne ze śrubami i podkładkami	kpl	4

1	2	3	4